# CONTENTS.

	PAGE
AN EXPLANATION,	17
DESIGNING A LOOM.	
The practical knowledge necessary to the designing of a	
loom,	18
Summary of the principal points to be considered in	
designing a loom,	18
THE DELINEATION OF CAMS AND TAPPETS FO SHEDDING.	R
The distinctive features in a pair of well-constructed cams	
for plain shedding,	20
Geometrical delineation of a cam for plain shedding,	20
A peculiarity in a pair of shedding cams and its	
explanation,	22
The difference in size between the two blades of a wyper	
and method of constructing them for actual work,	24
The construction of wypers or tappets for other than	
plain shedding,	27
Why always multiply the number of treads by four in order to find the number of divisions in the circle?	28
TOP ROLLER MOUNTINGS.	•
The top roller mounting for plain weaving, -	28
The top mounting for a three-leaf twill,	29
The top mounting for a four-leaf twill,	29
The treadles—a peculiarity, -	30
The position of the treadles in the loom for twill shedding,	31
How the skewed bevel wheels are made,	31
To find the relative number of teeth in the driving wheels	
for tappet shafts,	31

# DOBBY AND JACQUARD SHEDDING.

				PAGE
The Dobby machine, what is it?	-			- 33
The Jacquard machine,	-	-		- 34
The Jacquard machine explained and	illustre	ted,		- 34
How the machine is driven,	-		-	- 37
Another arrangement for moving the	cylinde	er,	-	- 39
The cylinder reversing movement, -	-		-	- 40
The single-lift machine,	-		-	- 42
The double-lift machine,	-		-	- 42
The twilling Jacquard,	-		-	- 44
Jacquard and tappet shedding compa	red, -		-	- 48
THE CONE P	ICK.			
The unsatisfactory condition of the m	oveme	nt,	-	- 49
Causes that lead to an unsatisfactor	ry mo	vement	in t	he
"cone" or "over" pick,			-	- 49
The length of tappet considered in re	lation t	to the l	ength	of
picking arm,			-	- 50
How the force applied by the tappet	should	be trai	nsmitt	$_{ m ed}$
to the shuttle,			-	- 51
The method of constructing the picki	ng cam	ι,	-	- 53
The vertical adjustment of the anti-fi			-	- 55
Two methods of driving the loom,		-	-	- 57
The sum of the whole matter,		-	-	- 57
THE UNDER	PICK.			
The under pick: its advantages over	the co	ne pick	ι,	- 58
The disadvantages of the under pi				are
being met,	_	-		. 60
Why always buffalo hide for pickers	?	-	-	- 6
BEATING UP TH	IE SH	OT.		
What actually takes place in the	making	of clo	th in	the
loom, -	-	-	-	- 6

	CONTEN	TS.				vii
TO COMBINE AND PRINCIPAL MOV						
The relative position of the	princi	nal na	rts of th	e loom.		PAGE 64
The rocking shaft, the swo	-			-		65
The cause of so much br			•	ds, and	its	
remedy,	-	•	-	-	-	66
The position of the crank s						67
The position of the tappe						
shaft, the treadles, an	d the	uprigh	t picki	ng shaf	t or	
spindle, -	-	•	-	-	-	69
The upright picking shaft,	-	-	-	-	-	71
The end frame,	-	*	-	-	•	74
THE POSITIVE	TAK	E-UP	MOVE	MENT.		
Its action,	-	-	-	-	-	74
The roller covering, -	-	-	-	-	-	75
Driving the take-up moven	nent,	-	-	-	-	75
The arrangement of the wh	eels in	the ta	ke-up n	noveme	nt, -	77
A continuous positive mov-	ement 1	not wa	nted,	-	-	79
THE NEGATIVE	E TAK	E-UP	MOVE	MENT	•.,	
Purposes for which it is b	etter a	dapte	l than	the posi	tive	
movement, -	-		-	-	-	79
THE LET	LOFF	MOVE	MENT			
As it is and might be,	011			•		80
The proper tension of the	rarn in	the lo	nm.	_	_	80
The put-back motion,	, 60111 111	viic 10	- -	_		81
•						
THE YARN PROT			TOMA	TIC ST	OP	
	OVEM	ENT.				
Its threefold purpose,		•		-	-	82
The momentum of its strok		-	-		-	82
Its construction and arrang			-	-	•	83
The length of the protector	r, -	•	-	-	•	84
The fly-reed protector,	-	-	-	•	-	84

	٠	٠	٠	
v	1	3	1	

## CONTENTS.

# STOP MOVEMENTS WHEN A WARP OR WEFT THREAD BREAKS.

				PAGE
When they become necessary,	-	-	-	84
THE SHUTTLE RELIEF MO	VEM	ENT.		
What experience has taught about it,	-	-	-	85
Its purpose,	-	-	-	85
What the movement is,	-	-	-	85
THE NORTHROP LO	OM.			
The two distinct methods at present be	ing er	nploye	d to	
increase the amount of work produce	d by	machin	ery,	87
The principal feature in the "new loom,"	-	~	-	87
The weft changer considered in relation	n to	the o	ther	
automatic movements,	-	-	-	88
Some of the new automatic movements,	-	-	-	90
HIGH SPEED LOOM	IS.			
Is the power-loom being driven as fast	as it	can be	with	
economy?		-	-	90
What is necessary in a high-speed loom?	~	-	•	91
A practical hint as to increasing the				
employed in the jute trade and the	maki	ng of o	other	
coarse fabrics,	-	-	-	92
MAKING THE LOO	М.			
How a well designed loom can be spoiled	in the	makin	g, -	92
How the frame-work should be fitted,	-	-	-	93
Gauge and jig in loom making, -	-	-	-	93
THE WEAVING SH	ED.			
The model loom factory,	_	_	_	94
The columns, -	_	_	_	94
With the shafting underground.		_	_	96

DRIVING THE POWER-	LOOM	<b>1</b> .		
The distribution of power from the gene	ratin	g station	to	PAGR
the loom,	-	- '		96
What has been done in the past to get a s	steady	moveme	ent	
for the power-loom, -	-	~		97
What is being done and what may be d	one to	lessen t	he	
vibration on the line shaft, -	-		-	100
The ideal method of driving power-looms,	-	-	-	102
SHAFTING, PULLEYS, LEATHE	R BE	LTS, A	ND	
ROPES.				
Driving power-looms,		-	-	102
Fixing the main shaft brackets, -	-	-	-	103
Erecting the shafting,	-	•		103
Levelling the pillow blocks,	-	-	-	104
Drums or pulleys,	-	-	-	104
To find the unknown quantity in pulleys,		-	-	104
To find the circumferential velocity of pul	leys,	-	-	105
The fast and loose pulleys and the friction	pull	eys—wh	ere	
each can be employed with most adv	antag	e, -	-	105
The convexity of pulleys,		-	-	106
Belts-their width and thickness, -	-	-	-	106
How the lap-jointed belts should run—the	lengt	th of lap		107
A belt clamp,	-	-	•	107
The necessity of squaring the ends of a bu	tt-joir	nted belt	, -	109
How a butt-jointed belt should be laced,	-	-	-	109
The management of belts, -	-	-	-	110
How to get the most power out of belts-	-the	direction	in	
which they should run,	-	-	-	111
The construction of rope pulleys, -	-	-	•	111
ERECTING AND FIXING LOOMS I	N TE	E FAC	roi	RY.
How the parts of the loom should be mark	ked,	-	-	113
How the main wheels should come into ge		_	-	113

 $\mathbf{x}$ 

			!	PAGE
The arrangement of the looms,	•		•	114
The main points to be observed in fixing lo	oms to	the fi	oor,	116
Another method,	-	-	-	117
A template necessary for this work, -	•	-	-	118
To find a proper bearing for the loom,	-	-	-	119
Points necessary to notice before starting	the loo	m,	-	119
WORKING THE LOC	OM.			
THE MECHANICAL DEPART	MENT.			
Some practical points worth noticing,	-	٠	-	119
To the young student,	-	-	-	121
The loom "knocking off"-to find the car	ıse,	-	-	122
The causes that make the loom knock off,			-	123
When the loom knocks off from a deficien-	cy of p	ower,	-	123
When the loom knocks off from an obstruc	tion to	the sh	uttle,	124
When the protector is at fault, -	-		-	12
The value of the ear in detecting what is	wrong,	-		12
Causes that throw the shuttle out of the l	oom,	-	-	12
The main principle that should guide the	mechai	nic,	-	120
Some things to be guarded against, -	-	-	-	120
WORKING THE LO	OM.			
THE TENTING, TACKLING, OR TUNIS	NG DEP	ARTMI	ENT.	
The power-loom tenter's work,	-		-	12'
Tackling,	-	-	-	128
The most important point in cloth making	z, -	-	-	129
Spreading the warp threads-what actu	ally ta	kes 1	olace	
amongst the yarn to cause the thi	reads t	o spre	ad —	
how it is done,	-	-	-	12
What part the shedding cams or wyper	rs play	in ma	king	
good cloth,	-	-	-	13
The lease rods—the part they play in mal	king go	od elo	th, -	13
The tension at which the yarn is held, an	d the a	djusti	ment	
of straps and cords,	-	-	-	13

CONTENTS.				хi
JACQUARD WEAVI	NG.			
Shedding with the Jacquard machine,	_			PAGE 133
Setting the machine to the comber-board,		-	-	134
Setting the cylinder,	_	_	_	136
Mounting the harness,	_	_	_	136
Preparing the lingues,	-	-		136
SOME DETAILS THAT SHOULD BE	! KNO	own i	RV A	T.T.
CONNECTED WITH WE			, , ,	
A peculiarity in the construction of the	shut	tle, and	the	
reason for it,	-		-	137
Management of the picking movement,	-	-	-	138
The use of the check-strap,		-		139
The intermediate or patent selvage—how		ormed,	-	140
HOW THE PATTERNS IN THE PRODUCED.	E CL	A HTC	RE	
Tappet, Dobby, and Jacquard shedding,	-	- '	-	143
Plain cloth,	-	-	-	144
Setting the heddles to the reed,	-	-	-	145
Regular twills,		-	-	146
The same twill with the draughts reverse		-	-	147
How the pattern should be turned, -	-	-	-	147
Irregular twills,	-	-	-	148
Common twills that are equally flushed on	both	sides of	the	
cloth,	-	-	-	148
The combination of common twill and pla			-	149
How the draughts and treading form the	ie pat	terns in	the	
cloth,			-	150
How the patterns are produced by the Ja			ne, -	152
How the cards are found and cut from th		ches,	-	154
A striking peculiarity in linen damask ele	oth,	-	-	155

#### CONTENTS.

## TEXTILE CALCULATIONS.

The different standards or bases of calculations used	d in	PAGE
different localities,		155
The "setts" or "porters" of the reed,	-	156
The calculation of warp yarns,	-	158
To find the weft,	-	159
An example showing how to find the quantity of warp	and	
weft in any given piece of cloth of any material,	-	160
To find the weight and cost of yarns,	-	161
Considerations that must be taken into account in de	eter-	
mining the price of cloth from that of the yarn,	-	162